

LANZONI

UTOATTREZZATURE



Building



Car Washing



Food

Pulvérisateurs et canons à mousse - Sprayers and foamers

www.lanzonionline.com



art. NBZ25

Nebulizzatore in ferro verniciato da 24 litri.

24 Lt. trailer-mounted Sprayer, painted metal.

art. NBZ50

Nebulizzatore in ferro verniciato da 50 litri.

50 Lt. trailer-mounted Sprayer, painted metal.

art. NBZ100

Nebulizzatore in ferro verniciato da 100 litri.

100 Lt. trailer-mounted Sprayer, painted metal.

Norma PED 97/23/CE

- pressione / *pressure* : 8 bar
- tubo di erogazione / *spiral output tube* : 10 m
- lancia terminale in acciaio INOX lunga 0.75 m / *end nozzle terminal in stainless steel, 0.75 mt length*

mod. **ECO** 24/50 litri : tubo 7 m – lancia PVC 60 cm
mod. **ECO** 24/50 litre : hose 7 m – PVC lance 60 cm



art. NBZX25

Nebulizzatore in inox AISI 304 da 24 litri.

24 Lt. trailer-mounted Sprayer, S.S. AISI 304.

art. NBZX50

Nebulizzatore in inox AISI 304 da 50 litri.

50 Lt. trailer-mounted Sprayer, S.S. AISI 304.

art. NBZX100

Nebulizzatore in inox AISI 304 da 100 litri.

100 Lt. trailer-mounted Sprayer, S.S. AISI 304.

Norma PED 97/23/CE

- pressione / *pressure* : 8 bar
- tubo di erogazione / *spiral output tube* : 10 m
- lancia terminale in acciaio INOX lunga 0.75 m / *end nozzle terminal in stainless steel, 0.75 mt length*



art. SCG25

Schiumogeno in ferro verniciato da 24 litri.
24 Lt. trailer-mounted Foamer, painted metal.

art. SCG50

Schiumogeno in ferro verniciato da 50 litri.
50 Lt. trailer-mounted Foamer, painted metal.

art. SCG100

Schiumogeno in ferro verniciato da 100 litri.
100 Lt. trailer-mounted Foamer, painted metal.

Norma PED 97/23/CE

- pressione / *pressure* : 8 bar
- tubo di erogazione / *output tube* : 10 m
- lancia terminale in acciaio INOX lunga 0.75 m / *end nozzle terminal in stainless steel, 0.75 mt length*

mod. **ECO** : tubo 3 m per i 24 l / 6 m per i 50 l – lancia PVC 60 cm
mod. **ECO** : hose 3 m for 24 litre / 3 m for 50 litre – PVC lance 60 cm



art. SCGX25

Schiumogeno in inox AISI 304 da 24 litri.
24 Lt. trailer-mounted Foamer, S.S. AISI 304.

art. SCGX50

Schiumogeno in inox AISI 304 da 50 litri.
50 Lt. trailer-mounted Foamer, S.S. AISI 304.

art. SCGX100

Schiumogeno in inox AISI 304 da 100 litri.
100 Lt. trailer-mounted Foamer, S.S. AISI 304.

Norma PED 97/23/CE

- pressione / *pressure* : 8 bar
- tubo di erogazione / *output tube* : 10 m
- lancia terminale in acciaio INOX lunga 0.75 m / *end nozzle terminal in stainless steel, 0.75 mt length*

Unità combinata in ferro verniciato da 25+25 l
25+25 Lt. trailer-mounted painted metal.

Norma PED 97/23/CE



25+25=50

Art.	Versione - Version
DBL25SS	Spray / Spray - Spray / Spray
DBL25SF	Spray / Schiuma - Spray / Foam
DBL25FF	Schiuma / Schiuma - Foam / Foam

Unità combinata in ferro verniciato da 50+50 l
50+50 Lt. trailer-mounted painted metal.

Norma PED 97/23/CE



50+50=100

Art.	Versione - Version
DBL50SS	Spray / Spray - Spray / Spray
DBL50SF	Spray / Schiuma - Spray / Foam
DBL50FF	Schiuma / Schiuma - Foam / Foam

Unità combinata in inox AISI 304 da 25+25 l
25+25 Lt. trailer-mounted S.S. AISI 304.

Norma PED 97/23/CE



25+25=50

Art.	Versione - Version
DBLX25SS	Spray / Spray - Spray / Spray
DBLX25SF	Spray / Schiuma - Spray / Foam
DBLX25FF	Schiuma / Schiuma - Foam / Foam

Unità combinata in inox AISI 304 da 50+50 l
50+50 Lt. trailer-mounted S.S. AISI 304.

Norma PED 97/23/CE



50+50=100

Art.	Versione - Version
DBLX50SS	Spray / Spray - Spray / Spray
DBLX50SF	Spray / Schiuma - Spray / Foam
DBLX50FF	Schiuma / Schiuma - Foam / Foam

Norma PED 97/23/CE

- pressione / pressure : 8 bar
- tubo di erogazione / output tube : 10 m
- lancia DOPPIA in acciaio INOX lunga 0.6 m / DOUBLE lance in stainless steel, 0.60 mt length



LC-1 : lancia inox 60 cm – *ss lance 60 cm*
LC-2 : lancia inox 75 cm – *ss lance 75 cm*
LC-3 : lancia inox 150 cm – *ss lance 150 cm*
LC-4 : lancia tel. 200 cm – *tel. lance 200 cm*
LC-5 : lancia inox 110 cm – *ss lance 110 cm*



LDB : lancia doppia in inox
LDB : *s.s. double lance*



B14 : raccordo con dado fresato 1/4" G
B14 : *milled nut for connections 1/4" G*



FLT : filtro in ingresso 0.7 mm
FLT : *inlet filter 0.7 mm*



UG-1 / 2 / 3 / 4 / 5 / 6 / 7 : ugello a ventaglio 110° - *fan nozzle 110°* 0,6 / 0,9 / 1,1 / 1,3 / 1,4 / 1,6 / 1,8 mm



UGS2 : ugello schiuma
UGS2 : *foam nozzle*



FLT1 : filtro per ugelli
FLT1 : *filter for nozzle*



TSCG : testina schiumogena
TSCG : *foam head*



SP7 / 10 : spirale RILSAN diam 8 mm – 7 m / 10 m
SP7 / 10 : *RILSAN spiral pipe diam 8 mm - 7 m / 10 m*



SPDB10 : spirale doppia 8 mm – 10 m
SPDB10 : *double spiral pipe 8 mm - 10 m*



TN3 : tubo 8x13 / 3 m – *8x13 hose / 3 m*
TN6 : tubo 8x13 / 6 m – *8x13 hose / 6 m*
TN-6/1 : tubo 10x15 / 6 m – *10x15 hose / 6 m*
TN10 : tubo 8x13 / 10 m – *8x13 hose / 10 m*
TN10/1 : tubo 10x15 / 10 m - *10x15 hose / 10 m*



RGN : regolatore con nipplo 1/4" G
RGN : *regulator with 1/4" G nipple*

PED 97 / 23 / CE
CE

Made in ITALY

LANZONI
AUTOATTREZZATURE

LANZONI AUTOATTREZZATURE di Lanzoni & Poli snc

Via al Palazzo, 10

42030 Vezzano sul Crostolo (RE) – ITALY

phone 0039 (0)522 606311

fax 0039 (0)522 601456

e-mail : lanzoni@lanzonionline.com

web site : <http://www.lanzonionline.com>